

Tensometric conveyor scales VTT 200-2300

Tensometric conveyor scales are designed for weighing sheet masterbatch.

Scope - pre-production of tire, cable, asbestos plants and rubber technical factories.



Tensometric conveyor scales VTT 200-2300

During the operation of the tensometric scales, the weighed material is fed onto the conveyor belt: a rubber mixture laid in folds or cut into sheets. When the required mass is reached, the process of supplying material to the scales stops. At the signal of the control system, the scales are switched on and the weighed portion of the material is fed into the rubber mixer.

Technical Specification:

Type of weigher stationary, transport, tensometric
Payload200
Weighing accuracy0,4% of the upper limit of weighing
Operating temperature range, ° C
Number of weight sensors, PCs
Power supply:
voltage, V
frequency, Hz50
Electric motor power, kW
The width of the conveyor belt, mm
The distance between the axes of the drums, mm, no m
Overall dimensions, mm, no more:
length
width
height
Weight, kg, no more

This product can be manufactured according to the technical specifications of the customer, taking into account its predetermined parameters and features.

Full cycle engineering services

Food Machinery

Machinery for tires, rubber, plastics manufacturing

Machinery for the chemical and oil and gas industry


Machinery for the perfumery and cosmetic industry

Modernization and automation of production

Non-standart equipment

Production of spare parts, components, assemblies

Outsourcing services - repair and maintenance of equipment



Policon JSCo 194 Lermontov Str, Omsk 644009, Russia Tel./Fax: +7 (3812) 36 74 12, 36 74 02, 48 48 30 e-mail: info@policon-rt.ru www.policon-rt.ru