

Butterfly valve (Model ZP)

Butterfly valve (Model ZP)

Butterfly valve is designed to regulate the flow of bulk ingredient from hopper equipment or conveyors



Features:

- polymer coating is used in production
- simplicity of design provides reliability and durability, ease of maintenance.
- it is completed with a manual, pneumatic or electric drive.
- integrates into automatic suspension systems for the preparation of rubber compounds.

Butterfly valve (Model ZP)

Technical Specification:

Model	Hole size, mm	Overall dimensions, mm			Weight,
		Length	Width	Height	kg
ZP - 1	95	250	220	77	4
ZP - 2	150	290	228	77	5
ZP - 3	200	340	278	77	6,5
ZP - 4	250	390	325	77	7,5
ZP - 5	300	440	375	77	9
ZP - 6	350	530	440	85	16
ZP - 7	400	580	530	85	20,5

This product can be manufactured according to the technical specifications of the customer, taking into account its predetermined parameters and features.

Food Machinery

Machinery for tires, rubber, plastics manufacturing


Modernization and automation of production

Non-standart equipment

Production of spare parts, components, assemblies

Outsourcing services - repair and maintenance of equipment

Global engineering solutions



Policon JSCo 194 Lermontov Str, Omsk 644009, Russia Tel./Fax: +7 (3812) 36 74 12, 36 74 02, 48 48 30

e-mail: info@policon-rt.ru www.policon-rt.ru