


Designed for the selection of bulk ingredients of rubber compounds from consumables and feeding them to the scales in the preparatory production of tire, cable, asbestos factories and rubber technical factories.



#### Features:

- The design of the feeder prevents caking of the material in the lower part of the hopper and ensures uniform, predetermined supply of the dosed material to the balance.
- The feeder housing is the lower section of the feed hopper with a built-in agitator and auger.
- The design of the screw, made in the form of blades and a helical surface, is individual for various types of materials.
- The drive is carried out by a gear motor with a frequency converter, providing smooth control of the speed of rotation of the screw and agitator.
- For more accurate dosing, a material cutter is installed on the discharge port of the feeder.
  - The feeder is made of stainless steel.







#### **Technical Specification:**

| Type of feeder         |       | screw    |
|------------------------|-------|----------|
| Power supply:          |       |          |
| voltage, Vfrequency Hz |       |          |
|                        | Screw | Diameter |

| Model | Transported material  | Size of door LxH, мм | Screw<br>diameter, mm | Diameter of agitator, mm |
|-------|---|----------------------|-----------------------|--------------------------|
| VP-1  | Zinc oxide  | 1 200 x 400          | 150                   | 300                      |
| VP-2  | White soot  | 1 200 x 400          | 200                   | 300                      |
| VP-3  | Sulfenamide C, Captax,<br>Altax, Diafen FP,<br>phthalic anhydride | 1 000 x 400          | 100                   | 300                      |
| VP-4  | Nitrol, Thiuram,<br>Nitrosodiphenylamine,<br>Chloroxyl, Sulfur    | 800 x 400            | 80 - 100              | 300                      |
| VP-5  | Sulfenamide M   | 1 000 x 400          | 100                   | 300                      |
| VP-6  | Modifier RU   | 800 x 400            | 100                   | 300                      |
| VP-7  | Neozone   | 1 000 x 400          | 100                   | 300                      |
| VP-8  | Rosin, HDPE   | 800 x 400            | 100 - 120             | 300                      |

This product can be manufactured according to the technical specifications of the customer, taking into account its predetermined parameters and features.

## Full cycle engineering services

### **Food Machinery**

Machinery for tires, rubber, plastics manufacturing

Machinery for the chemical and oil and gas industry


Machinery for the perfumery and cosmetic industry

Modernization and automation of production

Non-standart equipment

Production of spare parts, components, assemblies

Outsourcing services - repair and maintenance of equipment



Policon JSCo 194 Lermontov Str, Omsk 644009, Russia Tel./Fax: +7 (3812) 36 74 12, 36 74 02, 48 48 30 e-mail: info@policon-rt.ru www.policon-rt.ru